

SAXON WS-110

DESCRIPTION

Saxon WS-110 is a top quality low-odor organic solvent refined to meet the requirements of BS 245 Type A.

Saxon WS-110 is the essential decorators' aid when using oil- based coatings as it is suitable for general cleaning purposes, brush cleaning and will instantly solubilize and remove any splashes & spills from unintended surrounding surfaces including carpets & fabrics.

Saxon WS-110 is the ideal solvent for paint thinning due to its, compatibility with most types of commonly encountered domestic oil- based coatings, as it will not affect their drying time.

ADVANTAGES

- ✦ **Highly refined clear hydrocarbon solvent**
- ✦ **Essential aid during after using oil-based paints**
- ✦ **Cleans paint off brushes, rollers and stained fabrics**

MAIN PROPERTIES

PREPARED MIX PRODUCT	
Application temperature	+5°C to +30°C
Appearance	Water white
Pot life	12 hours at 10°C, 10 hours at 15°C, 1 hour at 25°C, 1 hour at 40°C,
Composition	Naphtha (petroleum) hydro-treated heavy
Solubility in oils	100%
Boiling point	150°C - 200°C
Evaporation Rate	65 (Et Et=1) - DIN 53170
Vapour pressure	< 5 kPa 20
Relative density	0.775 - 0.795
Viscosity	0.95 m ² /s 40
Form	Liquid
Specific Gravity	0.78 @ 25°C
Storage / Shelf life	Store for up to 12 months from date of manufacture in original, unopened packaging under cool, dry, conditions within the temperature range of +5°C to +30°C and out of direct sunlight.
Packing	Saxon WS-110 is available in 500ml, 1 litre, 2 litre & 4.5 litre bottles each fitted with a child resistant closure.

DIRECTIONS FOR USE





SAXON PAINTS.

IMPORTANT: Before using Saxon WS-110 refer to the relevant Health & Safety Data Sheet, available at www.saxonpaints.com

STORAGE AND HANDLING

Eliminate all sources of ignition, static electricity and formation of sparks must be prevented. Use explosion proof electric equipment. Wear full protective clothing for prolonged exposure and/or high concentrations. Contaminated clothing and shoes must be discarded. Contaminated rags and cloths must be put in fireproof containers for disposal. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

CLEANING

Spillages of Saxon WS-110 should be contained using absorbent pads or granules and then swept up & stored in clearly marked sealed containers for disposal in accordance with Local Authority regulations for flammable products – This product subject to special waste management controls.

PRECAUTIONS IN USE

For any application not covered please visit www.saxonpaints.com for advice. Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control. For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet available at www.saxonpaints.com



GENERAL INFORMATION

Apply all products in accordance with BS 6150: 2006 Code of practice for painting of buildings and BS 8000: Part 12: 1989 Code of practice for decorative wallcoverings and painting.

Every care is taken to ensure that all information provided on this Technical Data Sheet is accurate. Final results cannot be guaranteed by the manufacturer as it has no control over the conditions under which its products are applied.

For help or more information contact Saxon Paints or visit our website at www.saxonpaints.com Before using this product please ensure you have the latest information. The information is correct at date of issue February 2022.



WARRANTY

SAXON PAINTS warrant its title to the product, that the quality of the product conforms to Saxon Paints' specifications for such product in effect at the time of manufacture and that the product shall be delivered free of the rightful claim of any third person for infringement of any patent covering the product. This product is for professional use only. The applicators and operators shall be trained, experienced and have the capability and equipment to mix/stir and apply the coatings correctly and according to Saxon Paints' technical documentation. Applicators and operators shall use appropriate personal protection equipment when using this product. This guideline is given based on the current knowledge of the product. These are the only warranties that Saxon Paints makes and all other express or implied warranties, under statute or arising otherwise in law, from a course of dealing or usage of trade, including without limitation, any other warranty of fitness for a particular purpose or use, are disclaimed by Saxon Paints. Any claim under this warranty must be made by Buyer to Saxon Paints in writing within five (5) days of Buyer's discovery of the claimed defect, but in no event later than the expiration of the applicable shelf life of the product, or one year from the date of the delivery of the product to the Buyer, whichever is earlier. Buyer's failure to notify Saxon Paints of such non-conformance as required herein shall bar Buyer from recovery under this warranty. Any suggested deviation to suit the site conditions shall be forwarded to the responsible Saxon Paints' representative for approval before commencing the work.

LIMITATIONS OF LIABILITY

The information in this document is given to the best of Saxon Paints' knowledge. The information in this sheet is intended for guidance only and is based upon laboratory tests that Saxon Paints' believes to be reliable. Saxon Paints' products are considered as semi-finished goods and as such, products are often used under conditions beyond Saxon Paints' control like the quality or condition of the substrate, or the many factors affecting the use and application of the product. The product and related information are designed for users having the requisite knowledge and industrial skills in the industry and it is the end-user's responsibility to determine the suitability of the product for its own particular use and it shall be deemed that Buyer has done so, as its sole discretion and risk. Saxon Paints' does not accept any liability arising from any loss, injury or damage resulting from such use or the contents of this information. Variations in the application environment, changes in procedures of use, or extrapolation of data may cause unsatisfactory results. Minor product variations may be implemented in order to comply with local requirements. Users should always consult Saxon Paints' for specific guidance on the general suitability of this product for their needs and specific application practices. If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.

